



FLUXAF GRAFFI-CLEAN

TYPE

Waterbased graffiti remover is suitable for removing most kinds of graffiti, markers, ink, chewing gum from almost all surfaces in one step.

It does not contain any acids, lye, dangerous solvents (as NMP) or preservatives.

APPLICATION:

GRAFFI-CLEAN!® can be used against many types of pollution.

For removing graffiti, based on :

- oil paints, alkyd enamels
- latex and other waterbased paints
- stoving enamels
- acrylic based paints
- spray paints (car- and leatherpaint)

Also suitable for the removal of :

- chewing gum
- undesirable posters
- markers, pen, wax
- and many other things!

PROCESSING:

GRAFFI-CLEAN!® does not require any before or after treatment. GRAFFI-CLEAN!® can be used on almost any type substrate. When used properly the substrate will not be damaged. Wood, stone, marble etc. will not discolour and also almost all types of plastic will not be effected. Metals can, as always, be affected. The correct action period is essential. The longer GRAFFI-CLEAN!® is left on, the deeper it will penetrate the top level and (eventually) the lower level(s). Try to remove a small part of the contamination on a suitable test area.

Spray GRAFFI-CLEAN!® on the area which needs cleaning.

Remove the graffiti with a hard brush, water (possible high pressure), a clothe or a cleaning rag.

Do not use steel-wool for removal as this can result in rust.

A stainless steel sponge is suitable. We always recommend treatment of a test area first.

For more porous substrates these times can be longer, than smooth substrates.

If you want to remove graffiti without damaging the layer of paint underneath, spray GRAFFI-CLEAN!® on and remove after a few seconds with a moist cloth.

On very delicate substrates, spray GRAFFI-CLEAN!® on a moist cloth and gently wipe the area. Remove with water after a few seconds.

PRECAUTIONS:

GRAFFI-CLEAN!® is completely safe for humans and the environment. It causes no harmful fumes.

It is safe to use for professionals and DIY.

There are no specials precautions necessary, It can be used internally and externally no extra ventilation is needed.

Wear suitable PPE equipment.

The Safety Data Sheet is available on request.

TREATMENT:

The removed material (paint, glue etc.) must be disposed of according to local regulations.

The information in this data sheet is given to the best of our knowledge based upon laboratory tests & practical experience , however as the product is often used under conditions beyond our control , we cannot guarantee anything but the quality of the product itself.

We reserve the right to change the data supplied without notice.