

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lacq cooked yacht varnish (6000)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Product categories [PC]

PC9A - Coatings and paints, thinners, paint removers

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Vliegenthart B.V.

Street : Zuiderhavenweg 42

Postal code/city : 4004 JJ TIEL

Telephone : +31 (0)344 63 33 36

Telefax : +31 (0)344 63 16 16

1.4 Emergency telephone number

+31 (0)344 63 33 36 (During officehours: 08:30 - 17:00 hour.)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Flammable. · Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · Repeated exposure may cause skin dryness or cracking.

R 10 · R 52/53 · R 66

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Category 3 ; Harmful to aquatic life with long lasting effects.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02)

Signal word

Warning

Hazard statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of the reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container to chemicals waste depot.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Special rules for supplemental label elements for certain mixtures

EUH208 Contains 2-BUTANONE OXIME ; COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition/ information on ingredients

3.2 Mixtures

Hazardous ingredients

DE-AROMATISED KEROSENE ; REACH registration No. : 01-2119486659-16 ; EC No : 265-150-3; CAS No. : 64742-48-9

Weight fraction : 25 - 50 %
Classification 67/548/EEC : Xn ; R65 R66
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304

XYLENE ; REACH registration No. : 01-2119488216-32 ; EC No : 215-535-7; CAS No. : 1330-20-7

Weight fraction : 0 - 2,5 %
Classification 67/548/EEC : R10 Xn ; R20/21 Xn ; R65 Xi ; R36/37/38
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 3 ; H311 Asp. Tox. 1 ; H304 Acute Tox. 4 ; H332
Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

A MIXTURE OF BRANCHED AND LINEAR C7-C9-ALKYL -3-(3-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYL- ETHYL)-4-HYDROXYPHENYL)PROPIONATES ; REACH registration No. : 01-0000015648-61 ; EC No : 407-000-3; CAS No. : 127519-17-9

Weight fraction : < 1 %
Classification 67/548/EEC : N ; R51/53
Classification 1272/2008 [CLP] : Aquatic Chronic 2 ; H411

2-BUTANONE OXIME ; REACH registration No. : 01-2119539477-28 ; EC No : 202-496-6; CAS No. : 96-29-7

Weight fraction : < 0,5 %
Classification 67/548/EEC : Carc. Cat.3 ; R40 R43 Xi ; R41 Xn ; R21
Classification 1272/2008 [CLP] : Carc. 2 ; H351 Eye Dam. 1 ; H318 Acute Tox. 4 ; H312 Skin Sens. 1 ; H317

4- (1.1.3.3-TETRAMETHYLBUTHYL) PHENOL ; REACH registration No. : 01-2119541687-29 ; EC No : 205-426-2; CAS No. : 140-66-9

Weight fraction : < 0,5 %

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

Classification 67/548/EEC : N ; R50/53 Xi ; R41 Xi ; R38
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410
4-TERT-BUTYLPHENOL ; REACH registration No. : 01-2119489419-21 ; EC No : 202-679-0; CAS No. : 98-54-4
Weight fraction : < 0,5 %
Classification 67/548/EEC : Repr. Cat.3 ; R62 N ; R51/53 Xi ; R41 Xi ; R37/38
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1C ; H314 Eye Irrit. 2 ; H319 STOT SE 3 ; H335 Aquatic Chronic 2 ; H411
COBALT BIS(2-ETHYLHEXANOATE) ; REACH registration No. : 01-2119524678-29 ; EC No : 205-250-6; CAS No. : 136-52-7
Weight fraction : < 0,5 %
Classification 67/548/EEC : N ; R50/53 Repr. Cat.3 ; R62 R43
Classification 1272/2008 [CLP] : Repr. 2 ; H361f Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

3.3 Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

If possible, remove contactlenses. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do not induce vomiting. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam. Extinguishing powder. Carbon dioxide (CO₂). Sand. Water mist

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

Unsuitable extinguishing media

High power water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Do not allow run-off from fire-fighting to enter drains or water courses. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling



Protective measures

Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment. (see chapter 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Avoid the forming of inflammable or explosive concentrations of vapour in the air and exposure concentrations higher than permitted, Comply with the health and safety at work laws.

Fire prevent measures

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

Technical measures and storage conditions

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.

Requirements for storage rooms and vessels

Keep container tightly closed. Ensure adequate ventilation of the storage area. Restrict access to stockrooms.

Hints on joint storage

Keep away from

Keep away from ignition sources. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : STEL (EC)

Limit value : 100 ppm / 442 mg/m³

Remark : H

Version : 08-06-2000

Limit value type (country of origin) : TWA (EC)

Limit value : 50 ppm / 221 mg/m³

Remark : H

Version : 08-06-2000

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

Personal protection equipment

Eye / face protection



Eye glasses with side protection

Skin protection

Hand protection



Long Gloves NR (natural rubber, natural latex) Recommended Thickness DIN EN 374

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

Body protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Suitable protective clothing : Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. By spraying: air fed respirator. By other operations than spraying: in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : honey like
Odour : Characteristic.
Odor Threshold value Not determined

Safety relevant basis data

Physical state :			liquid	
Melting point / melting range :			No data available	
Boiling temperature / boiling range :	(1013 hPa)		150	°C
Decomposition temperature :	(1013 hPa)		Not determined	
Evaporation rate			Not determined	
Flash point :			36	°C
Ignition temperature :			240	°C
Flammability (gas, solid)			Not determined	
Lower explosion limit :			Not determined	
Upper explosion limit :			Not determined	
Explosive properties			Not determined	
Density :	(20 °C)	ca.	0,918	g/cm ³
Water solubility :	(20 °C)		insoluble	
PH value :			not applicable	
Flow time :	(20 °C)		70 - 90	s
Oxidising properties			Not determined	
Partition coefficient n-octanol/water		Not determined		DIN-cup 4 mm

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7 and 8).

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY HYDROGEN TREATED NAPHTHA ; CAS No. : 64742-48-9)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (4-TERT-BUTYLPHENOL ; CAS No. : 98-54-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	2951 mg/kg
Parameter :	LD50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	8700 mg/kg

Acute dermal toxicity

Parameter :	LD50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY HYDROGEN TREATED NAPHTHA ; CAS No. : 64742-48-9)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 4 mg/kg
Parameter :	LD50 (4-TERT-BUTYLPHENOL ; CAS No. : 98-54-4)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	2288 mg/kg
Parameter :	LD50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	2000 mg/kg

Acute inhalation toxicity

Parameter :	LC50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY HYDROGEN TREATED NAPHTHA ; CAS No. : 64742-48-9)
Exposure route :	Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

Species : Rat
Effective dose : > 13,1 mg/l
Exposure time : 4 h
Parameter : LC50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route : Inhalation
Species : Rat
Effective dose : 6350 mg/l

11.3 Other adverse effects

Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea. Delayed reactions possible (breathing problems, coughs, asthma) Eye contact: irritation. Inhalation/eye contact: in high concentrations irritating to the mucous membranes, narcotic effect and influence on power of reaction and loss of coordination possible.

11.4 Additional information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : Acute (short-term) fish toxicity (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY HYDROGEN TREATED NAPHTHA ; CAS No. : 64742-48-9)
Species : Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : > 1000 mg/l
Exposure time : 96 h

Acute (short-term) daphnia toxicity

Parameter : Acute (short-term) daphnia toxicity (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY HYDROGEN TREATED NAPHTHA ; CAS No. : 64742-48-9)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : > 1000 mg/l
Exposure time : 48 h

Acute (short-term) algae toxicity

Parameter : Acute (short-term) algae toxicity (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY HYDROGEN TREATED NAPHTHA ; CAS No. : 64742-48-9)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 1000 mg/l
Exposure time : 72 h

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Further ecological information

Additional information

Product should not be released into water without pre-treatment (biological sewage plant).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. The generation of waste should always as far as possible be avoided, or be limited to a minimum. Disposal of this product, solutions and any by-products should at all times be in accordance with applicable legislation in the field of environmental protection and waste disposal legislation and any other regional or local regulations.

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT RELATED MATERIAL

Sea transport (IMDG)

PAINT RELATED MATERIAL

Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3

Classification code : F1

Hazard identification number (Kemler

No.) : 30

Tunnel restriction code : D/E

Special provisions : 640E · LQ 7 · E 1 · Transport in containers with max. 450 litres contents are not subject to the regulations of ADR/RID.

Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3

EmS-No. : F-E / S-E

Special provisions : LQ 5 I · E 1 · IMDG 2.3.2.5 (<= 30 l)

Hazard label(s) : 3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.5 Relevant R-, H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq cooked yacht varnish
Revision date : 19.06.2014
Date of print : 16-09-2014

Version : 1.0.0

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
10	Flammable.
20/21	Harmful by inhalation and in contact with skin.
21	Harmful in contact with skin.
36/37/38	Irritating to eyes, respiratory system and skin.
37/38	Irritating to respiratory system and skin.
38	Irritating to skin.
40	Limited evidence of a carcinogenic effect.
41	Risk of serious damage to eyes.
43	May cause sensitization by skin contact.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
62	Possible risk of impaired fertility.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

Make sure that employees are aware of the safety risk. People wearing breathing apparatus must be appropriately trained.

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
