

Trade name :	Lacq hardwoodoil		
Revision date :	11.09.2014	Version (Revision) :	3.0.0 (2.0.0)
Date of print :	11-09-2014		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lacq hardwoodoil (6200)

- **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses
 - Product categories [PC]

PC9A - Coatings and paints, thinners, paint removers Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

1.3 Details of the supplier of the safety data sheet Supplier (manufacturer/importer/only representative/downstream

user/distributor)

Vliegenthart B.V.

Street : Zuiderhavenweg 42

Postal code/city: 4004 JJ TIEL

Telephone : +31 (0)344 63 33 36

Telefax : +31 (0)344 63 16 16

1.4 Emergency telephone number +31 (0)344 63 33 36 (During officehours: 08:30 - 17:00 hour.)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC None

Classification according to Regulation (EC) No. 1272/2008 [CLP] None

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

 EUH208
 Contains HYDROCARBONS - TERPENE ; COBALT BIS(2-ETHYLHEXANOATE).May produce an allergic reaction.

 EUH210
 Safety data sheet available on request.

2.3 Other hazards

None

SECTION 3: Composition/ information on ingredients

3.2 Mixtures

Hazardous ingredients



Trade name : Revision date : Date of print :	Lacq hardwoodoil 11.09.2014 11-09-2014	Version (Revision) :	3.0.0 (2.0.0)
	DEACH registration No. • 01-2110552062-40	• EC No. • 222 269 1• CAS No. • 9000 41 7	

TERPINEOL ; REACH registration No. : 01-2119553062-49 ; EC No : 232-268-1; CAS No. : 8000-41-7 Weight fraction : 1 - 2,5 % Classification 67/548/EEC : Xi ; R36/38 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 Classification 1272/2008 [CLP] : HYDROCARBONS - TERPENE ; REACH registration No. : 01-2119980606-28 ; EC No : 273-309-3; CAS No. : 68956-56-9 Weight fraction : 0,1 - 1 % Classification 67/548/EEC : R10 N; R51/53 R43 Xn; R65 Xi; R36/38 Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411 COBALT BIS(2-ETHYLHEXANOATE) ; REACH registration No. : 01-2119524678-29 ; EC No : 205-250-6; CAS No. : 136-52-7 Weight fraction : 0,1 - 0,25 % Classification 67/548/EEC : N; R50/53 Repr. Cat.3; R62 R43 Classification 1272/2008 [CLP] : Repr. 2 ;H361f Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

3.3 Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

If possible, remove contactlenses. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After indestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do not induce vomiting. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - Suitable extinguishing media



Trade name :	Lacq hardwoodoil		
Revision date :	11.09.2014	Version (Revision) :	3.0.0 (2.0.0)
Date of print :	11-09-2014		

Alcohol resistant foam. Extinguishing powder. Carbon dioxide (CO2). Sand. Water mist

Unsuitable extinguishing media

High power water jet.

5.2 Special hazards arising from the substance or mixture Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a heath hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Do not allow run-off from fire-fighting to enter drains or water courses. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling



Protective measures

Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment. (see chapter 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Avoid the forming of inflammable or explosive concentrations of vapour in the air and exposure concentrations higher than permitted, Comply with the health and safety at work laws.

Fire prevent measures

Product is a/contains drying oil. Materials with drying oil can self-ignite by overheating: Let cloths and rags dry

Page : 3 / 8



Trade name :	Lacq hardwoodoil		
Revision date :	11.09.2014	Version (Revision) :	3.0.0 (2.0.0)
Date of print :	11-09-2014		

unfolded or soak with water.

7.2 Conditions for safe storage, including any incompatibilities Technical measures and storage conditions

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.

Requirements for storage rooms and vessels

Keep container tightly closed. Ensure adequate ventilation of the storage area. Restrict access to stockrooms.

Hints on joint storage

Keep away from

Keep away from ignition sources. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protection equipment

Eye / face protection



Eye glasses with side protection

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

Hand protection



Long Gloves PVC (Polyvinyl chloride) PE (polyethylene) NR (natural rubber, natural latex) Recommended Thickness DIN EN 374

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Page : 4 / 8



Trade name :	Lacq hardwoodoil		
Revision date :	11.09.2014	Version (Revision) :	3.0.0 (2.0.0)
Date of print :	11-09-2014		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

•	-	-	-		
Colour :	Amber				
Odour :	Characteristic.				
Odor Threshold value	Not determined				
Safety relevant basis d	ata				
Physical state :			liquid		
Melting point / melting range :			No data available		
Boiling temperature / boiling r	ange (1013 hPa)	>	300	°C	
Decomposition temperature :	(1013 hPa)		Not determined		
Evaporation rate			Not determined		
Flash point :		>	250	°C	CC
Ignition temperature :			Not determined		
Flammability (gas, solid)			Not determined		
Lower explosion limit :			Not determined		
Upper explosion limit :			Not determined		
Explosive properties			Not determined		
Density :	(20 °C)	ca.	0,946	g/cm ³	
Water solubility :	(20 °C)		Not determined		
PH value :			not applicable		
Viscosity :	(20 °C)		Not determined		
Oxidising properties			Not determined		
Partition coefficient n- octanol/water	Not determined				
Other information					

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available. 10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7 and 8).

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.



Trade name : **Revision date :** Date of print :

Lacg hardwoodoil 11.09.2014 11-09-2014

Version (Revision) :

3.0.0 (2.0.0)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects Acute oral toxicity

Parameter :	LD50 (TERPINEOL ; CAS No. : 8000-41-7)
Exposure route :	Oral
Species :	Mouse
Effective dose :	5420 mg/kg
Parameter :	LD50 (TERPINEOL ; CAS No. : 8000-41-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	4300 mg/kg
Parameter :	LD50 (COBALT CARBOXYLATE ; CAS No. : 13586-82-8)
Exposure route :	Oral
Species :	Rat
Effective dose :	900 - 1200 mg/kg
Acute dermal toxicity	
Parameter :	LD50 (TERPINEOL ; CAS No. : 8000-41-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 3000 mg/kg
Acute inhalation toxicity	
Parameter :	LC50 (COBALT CARBOXYLATE ; CAS No. : 13586-82-8)
Exposure route :	Inhalation
Species :	Rabbit
Effective dose :	3400 - 5500 mg/m ³
Phototoxicity	
Additional information	

Phototoxicity Additional information

According to known data, also after prolonged contact, no hazard to health has occured

11.4 Additional information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.



Trade name :	Lacq hardwoodoil		
Revision date :	11.09.2014	Version (Revision) :	3.0.0 (2.0.0)
Date of print :	11-09-2014		

12.5 Results of PBT and vPvB assessment No information available.

No information available.

12.6 Other adverse effects

No information available.

12.7 Further ecological information Additional information

Product should not be released into water without pre-treatment (biological sewage plant).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

14.4 Packing group

No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user None

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information



Trade name :	Lacq hardwoodoil		
Revision date :	11.09.2014	Version (Revision) :	3.0.0 (2.0.0)
Date of print :	11-09-2014		

16.1 Indication of changes

02. Special rules for supplemental label elements for certain mixtures \cdot 02. Labelling (67/548/EEC or 1999/45/EC) - Hazard components for labelling \cdot 02. Special provisions concerning the labelling of certain mixtures \cdot 03. Hazardous ingredients

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.5 Relevant R-, H- and EUH-phrases (Number and full text)

1226	Flammable liquid and vapour.
1227	Combustible liquid.
1304	May be fatal if swallowed and enters airways.
1315	Causes skin irritation.
	May cause an allergic skin reaction.
	Causes serious eye irritation.
H361f	Suspected of damaging fertility.
1400	Very toxic to aquatic life.
-411	Toxic to aquatic life with long lasting effects.
1412	Harmful to aquatic life with long lasting effects.
LO	Flammable.
36/38	Irritating to eyes and skin.
13	May cause sensitization by skin contact.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
52	Possible risk of impaired fertility.
55	Harmful: may cause lung damage if swallowed.

16.6 Training advice

Make sure that employees are aware of the safety risk. People wearing breathing apparatus must be appropriately trained.

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.