



Lacq Natuleum®

Lacq Natuleum® is a traditionally cooked product consisting of natural waxes, resins and oils for superb protection of your outdoor wood. Lacq Natuleum® remains flexible for a long time, penetrates very well in most types of wood and has an excellent moisture-resistance ability. It has a natural deep brown/black colour.

Because Natuleum® contains no VOC, consequently there is no loss by evaporation and 100% of the material remains on the wood after drying.

Application:

For use on all types of wood, for resistance to water penetration and rot. Especially suitable as a replacement for carbolineum and coal tar. To be used on, wooden pilings, sheds, barns, fencing, piers, mooring posts, floodgates etc. Due to the natural brown/black colour it is excellent for refreshing or decorating wood work, for example sleeper paint and creosote.

Recommendation:

Especially filling all cracks and wind tears with Natuleum® is the perfect prevention of rot from within. Even after years, it remains elastic and retains its water-repellent function.

Treatment:

- Surface must be dry, dust-free and free from any surface contaminants ie oil or grease, remove any loose parts. Sanding is not necessary, only if a smooth result is desired.
- Stir thoroughly before use.
- Apply using a flat brush or tar brush; to ensure a neat finish, apply Natuleum in the length-wise direction of the wood grain.
- Second layer can only be applied after complete drying of the first coat. We recommend applying three layers on untreated wood.

Lacq Natuleum® dries slowly, especially in cold weather. It should therefore preferably be applied in the summer. In direct sun, Natuleum® draws into the wood very well. Depending on the ambient conditions at time of the application, drying time is between 24 – 48 hours. The wood should be properly dry and not treated beforehand with a sealant coating.

If the wood has already been treated with a wood preservative such as, for example, carbinoleum, this is acceptable. All traces of varnish type products should be removed completely from the surface of the wood before applying Natuleum®.

Number of layers:

During a first treatment it is recommended to apply two or three coats, especially where the Natuleum® soaks into the wood. Never dilute Natuleum®, apply at least at room temperature, stir well to ensure product consistency so the product is absorbed into the wood in a uniform manner. The second coat should only be applied after the first coat has thoroughly dried or has sufficiently absorbed into the wood. Even with warm and dry weather one should take into account approximately 2 days.

Touch-ups and maintenance:

Natuleum® can be applied upon application for many years without the risk of cracking or peeling. If the coatings becomes too thick, they can be scraped off, with a linbide scraper. After removal, apply a new application.

Coverage:

Approx 6 m² per litre. (Dependent upon the absorbency and surface profile of the wood.)

Clean tools with white spirit.

Shelf life:

At least 2 years from the production date if stored at a temperature between 5°C and 30°C in unopened original packaging